

ZILMET ULTRA PRO

Potable Tanks with Replaceable Bladder



- These tanks offer unlimited service as the bladder is easily replaceable
- A full range of replaceable bladder expansion tanks ranging from 2 gallons up to 260 gallons

VERTICAL MODELS - 10BAR

Model Number:	Volume: (Gal)	Tank Weight: (Lbs)	Connection Size: (NPT)	Shipping Dimensions: (LxWxH)	Acceptance Volume: (Gal)	UPC Code: (801985)	List Price: (US \$)
ZUP8	2.1	2.6	3/4"	13.8" x 8.1" x 8.3"	1.5	5041566	\$69.06
ZUP12V	3.2	3.2	3/4"	11" x 12.6" x 11.1"	2.4	5041573	\$76.02
ZUP18V	5	3.8	3/4"	10.9" x 16.5" x 11"	3.7	5041580	\$85.14
ZUP24V	6.3	5.3	1"	19.4" x 11" x 11.3"	4.6	5041597	\$90.36
ZUP50V	13.2	9.9	1"	30.9" x 15.2" x 15.2"	9.7	5040668	\$313.14
ZUP60V	15.9	10.2	1"	34.3" x 15.4" x 15.8"	11.7	5041610	\$327.78
ZUP80V	21.1	11.6	1"	32.9" x 18.1" x 18.4"	15.5	5040767	\$397.56
ZUP100V	26.4	15.8	1 1/2"	38.2" x 18.1" x 18.4"	19.4	5041641	\$510.60
ZUP200V	52.8	36.5	1 1/2"	51.3" x 20.9" x 22.9"	38.8	5042013	\$836.94
ZUP300V	79.3	51	1 1/2"	24.8" x 24.8" x 55.7"	58.3	5042006	\$883.44
ZUP500V	132.1	79.7	1 1/2"	29.5" x 29.5" x 63.4"	97.2	5046462	\$1,722.72
ZUP750V	198.1	142.7	1 1/2"	29.5" x 29.5" x 83.7"	134	5046448	\$3,110.64
ZUP1000	264.2	208.7	1 1/2"	33.5" x 33.5" x 84.6"	154.2	5040491	\$6,263.88

HORIZONTAL MODELS - 10BAR

Model Number:	Volume: (Gal)	Tank Weight: (Lbs)	Connection Size: (NPT)	Shipping Dimensions: (LxWxH)	Acceptance Volume: (Gal)	UPC Code: (801985)	List Price: (US \$)
ZUP24H*	6.3	5.3	3/4"	10.6" x 11.4" x 19.1"	4.6	5038337	\$111.00
ZUP50H*	13.2	9.9	1"	15" x 16.1" x 22.1"	9.7	5038306	\$313.14
ZUP60H	15.9	10.2	1"	15" x 16.1" x 25.2"	11.7	5038214	\$327.78
ZUP80H	21.1	11.6	1"	17.7" x 18.9" x 25.2"	15.5	5038221	\$397.56
ZUP100H	26.4	15.8	1"	17.7" x 18.9" x 28.7"	19.4	5038238	\$510.60
ZUP200H	52.8	36.5	1 1/2"	21.7" x 22.8" x 38.8"	38.8	5038245	\$836.94
ZUP300H	79.3	51	1 1/2"	24.8" x 26" x 44.9"	58.3	5041542	\$1,060.14

* with feet

Description:	Material:
shell	carbon steel
connections	carbon steel
fixed membrane	butyl
color	White with epoxy powder coating

Operating Conditions:	
factory precharge	28 psi
max. working pressure	150 psi
max. operating temperature	210° F
warranty	5 years